SAFETY DATA SHEET

BLACK MAGIC FOAMING ALL WHEEL CLEANER

Infosafe No.: LQ97J ISSUED Date : 09/01/2019 ISSUED by: <u>G</u>riffiths Equipment Ltd

1. IDENTIFICATION

GHS Product Identifier BLACK MAGIC FOAMING ALL WHEEL CLEANER

Company Name Griffiths Equipment Ltd

Address 22-24 Olive Road Penrose Auckland 1061 New Zealand

Telephone/Fax Number Tel: +64 9 5254575

Emergency phone number 0800 764 766 (All Hours)

Emergency Contact Name www.griffithsequipment.co.nz

E-mail Address sales@griffithsequipment.co.nz

Recommended use of the chemical and restrictions on use Tire and wheel cleaner.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand. Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

2.1.2A (2 Warning) - Flammable aerosols (2)
6.3A Substance that is irritating to the skin
6.6A Substance that is known or presumed to be a human mutagen
6.7A Substance that is known or presumed to be a human carcinogen
8.3A Substance that is corrosive to ocular tissue
9.1C Substance that is harmful in the aquatic environment

Signal Word (s) DANGER

Hazard Statement (s)

H223 Flammable aerosol.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H340 May cause genetic defects.
H350 May cause cancer.
H412 Harmful to aquatic life with long lasting effects.

Pictogram (s) Flame,Health hazard,Corrosion



Precautionary statement – Prevention

P102 Keep out of reach of children.

P103 Read label before use.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

Precautionary statement – Response

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see on this label).

P101 If medical advice is needed, have product container or label at hand.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statement – Storage

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50ºC/122ºF.

Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

Other Information

Note: Pressurised container may burst if heated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Propylene glycol	57-55-6	5-10 %
Petroleum gases, liquefied	68476-85-7	5-10 %
Benzenesulfonic acid, dimethyl-, sodium salt	1300-72-7	5-10 %
Butanedioic acid, sulfo-,1,4-bis(2-ethylhexyl) ester, sodium salt	577-11-7	5-10 %
Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)omega hydroxy-	9016-45-9	1-5 %
Ingredients determined not to be hazardous, including water.		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Unlikely due to form of product. However, if ingested, do not induce vomiting. Wash out mouth thoroughly with water. If symptoms develop seek medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use dry chemical, carbon dioxide, sand, earth, water spray or regular foam.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes including carbon oxides.

Specific Hazards Arising From The Chemical

Contents under pressure - cans can explode in a fire. This product is flammable. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

2YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Extinguish or remove all sources of ignition and stop leak if safe to do so. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. Place inert, Non-combustible absorbent material onto spillage. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations. Spillage can be slippery.

7. HANDLING AND STORAGE

Precautions for Safe Handling

FLAMMABLE. VAPOUR OR GAS REDUCES OXYGEN FOR BREATHING. IN CONFINED SPACES MAY CAUSE ASPHYXIATION. Wear appropriate personal protective equipment and clothing to prevent exposure. Avoid exposure. Do not handle until all safety precautions have been read and understood. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Do not expose can to temperatures exceeding 50°C. Protect containers against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS 2278.1 Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive.

Storage Temperatures

Do not store at temperatures over 50°C or in direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Petroleum gases, liquefied (LPG) TWA: 1000 ppm, 1800 mg/m³

Propylene glycol TWA: 150 ppm, 474 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eighthour working day, for a five-day week.

Source: Workplace Exposure Standards and Biological Exposure Indices.

Biological Limit Values

No biological limits allocated.

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 2865 Australian Standard Safe working in a confined space, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/ face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as natural rubber, neoprene or PVC. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Aerosol	Appearance	Clear amber liquid
Colour	Clear amber	Odour	Cherry odour
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	>100°C	Solubility in Water	Miscible in water.
рН	7.8	Vapour Pressure	Not available
Vapour Density (Air=1)	Not available	Evaporation Rate	Not available
Odour Threshold	Not available	Viscosity	Not available
Volatile Component	VOC content : 7.8%	Partition Coefficient: n- octanol/water	Not available
Density	8.60 lb/gal	Flash Point	Not available
Flammability	Flammable	Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available	Flammable Limits - Upper	Not available
Explosion Properties	Not available	Relative density	1.03 - 1.05

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling.

Reactivity and Stability Reacts with incompatibles.

Conditions to Avoid Heat, open flames and other sources of ignition.

Incompatible materials Strong oxidizing agents.

Hazardous Decomposition Products

Under fire conditions this product may emit toxic and/or irritating fumes including carbon oxides.

Hazardous Polymerization

Not available

11. TOXICOLOGICAL INFORMATION

Toxicology Information

Toxicity data for material and the available acute toxicity data for the ingredients is given below:

Acute Toxicity - Oral

ATEmix (oral) 9803 mg/kg

Water LD50 (Rat): >90 mg/kg

Benzenesulfonic acid, dimethyl-, sodium salt LD50 (Rat): 1000 mg/kg

Butanedioic acid, sulfo-,1,4-bis(2-ethylhexyl) ester, sodium salt LD50 (Rat): 1900 mg/kg

Propylene glycol LD50 (Rat): 20 g/kg

Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-LD50 (Rat): 1310 mg/kg LD50 (Rat): 2590 mg/kg

Acute Toxicity - Inhalation ATEmix (inhalation-gas) 3786540 mg/l

Acute Toxicity - Dermal ATEmix (dermal) 28030 mg/kg

Butanedioic acid, sulfo-,1,4-bis(2-ethylhexyl) ester, sodium salt LD50 (Rabbit): 10000 mg/kg

Propylene glycol LD50 (Rabbit): 20800 mg/kg

Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-LD50 (Rabbit): 1780 μL/kg LD50 (Rabbit): 2590 mL/kg

Ingestion

Ingestion unlikely due to form of product.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes eye damage. Eye contact will cause stinging, blurring, tearing, severe pain and possible burns, necrosis, permanent damage and blindness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

May cause genetic defects. Classified as Known or presumed to induce heritable mutations.

Carcinogenicity

May cause cancer. Classified as a Known or presumed human carcinogen.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Persistence and degradability Not available

Mobility Disperses in water.

Petroleum gases, liquefied Partion coefficient: <=2.8

Bioaccumulative Potential Not available

Other Adverse Effects Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a flammable substance contained in a pressurised container.

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

Do not pierce, burn, cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations

14. TRANSPORT INFORMATION

Transport Information

This material is classified as Dangerous Goods Division 2.1 - Flammable Gases

- Must not be loaded in the same freight container or on the same vehicle with:
- Class 1: Explosives
- Class 3: Flammable liquids
- Division 4.2: Spontaneously combustible substances
- Division 4.3: Dangerous when wet substances
- Division 5.1: Oxidising substances

- Division 5.2: Organic peroxides - Class 7: Radioactive materials unless specifically exempted. Must not be loaded in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with: - Division 4.1 Flammable solids Marine Transport (IMO/IMDG): Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. Class/Division: 2 UN No: 1950 **Proper Shipping Name: AEROSOLS** Packing Group: Not applicable EMS: F-D, S-U Special Provisions: 63, 190, 277, 327, 344, 381, 959 Air Transport (ICAO/IATA): Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. Class/Division: 2.1 UN No: 1950 Proper Shipping Name: Aerosols, flammable Packing Group: Not applicable Packaging Instructions (passenger & cargo): 203 Packaging Instructions (cargo only): 203 Hazard Label: Flammable Gas Special Provisions: A145, A167, A802 **U.N. Number** 1950 **UN proper shipping name AEROSOLS** Transport hazard class(es) 2.1 Hazchem Code 2YF **IERG Number** 49 **IMDG Marine pollutant** No

Transport in Bulk Not available

Special Precautions for User Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Group Standard: Aerosols (Flammable, Toxic [6.7]) Group Standard 2006

HSNO Approval Number HSR002517

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Created: January 2019

References

Workplace Exposure Standards and Biological Exposure Indices.

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.